

MANNINGTON COMMERCIAL

MANNINGTON M-Guard 798 ADHESIVE

Description: M-Guard 798 is specifically formulated for use with MANNINGTON'S Integra HP™ RE backing system only. M-Guard 798 is a very high solids ultra premium acrylic-based permanent adhesive that is non-flammable and solvent free. M-Guard 798 provides a strong moisture and alkali resistant bond and is vinyl compatible. M-Guard 798 can be used for wood and concrete surfaces above, on and below grade as well as a variety of other substrates. M-Guard 798 is freeze thaw stable and has permanent antimicrobial protection.

Uses: M-Guard 798 is the appropriate adhesive for installing MANNINGTON'S Integra HP™ Re vinyl backing system. May be used for installations over concrete subfloors with up to 8 pounds moisture vapor emissions as determined by Calcium Chloride Test (ASTM F 1869), or 85% relative humidity (ASTM F 2170) and pH of 10. ***M-Guard 798 is not recommended for concrete slabs where hydrostatic pressure or renewable moisture sources exist. (See warranty for details)***

Specifications:

M-Guard 798:	Acrylic permanent adhesive
Quantities:	4 gallon pail (Order Code MG798 – 57873)
Backing Code:	IR-HP
Unit Weight:	40 lbs
Color:	Grey – Red and Blue Tracers
Flammability:	Non-Flammable
VOC	0 – Calculated
GLP#	GLP60001
Shelf Life:	1 year from manufacture date on unopened containers
Warranty:	Limited Lifetime performance warranty
Coverage:	12 – 15 yards per gallon on smooth floors using a 1/16 x 1/16x 1/16 square notch trowel