

*new* Work.

magna®

18017 rose chocolate

The ideal fit for any commercial space.

Magna offers exceptional durability, premium value and ease of installation making it the ideal fit for multiple applications.

**MANNINGTON**  
COMMERCIAL

**MAGNA**














































**PERFORMANCE ATTRIBUTES**

- 6' (1.83m)
- Quantum Guard™ is a protective urethane wearlayer providing the ultimate ease in maintenance for resilient floors
- Quantum Guard™ is applied with UV (ultra violet) curing which may reduce the need for polish in normal traffic areas. Polish may be required in areas adjacent to exterior doors, extremely high traffic locations or if any irregular wear begins to show due to traffic
- Chemically seal or heat weld at seams for aseptic and integral surface (heat-weld is preferred method for healthcare and high traffic environments)
- ASTM F-1303 Type 2, Class 1, Grade A
- Limited 5-Year Commercial Warranty

**ENVIRONMENTAL ATTRIBUTES**

- Certified NSF-332 Gold
- Certified under FloorScore – an independent 3rd Party IAQ verification system for low emitting flooring. Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3
- ISO 9001 and 14001 registered manufacturing facility
- Manufactured in Salem, NJ 08079 and can contribute to LEED Credit 5.1 and 5.2
- Adhesives meet VOC content limit of SCAQMD Rule #1168 and can contribute to LEED IEQ Credit 4.1
- Made in USA

MAGNA (coordinated with Mannington's Edge Wall Base Collection)

			
	18000 granite white	18001 graystone	18002 graphite
	935 cameo white 	910 glacier 	942 bedrock 
	910 glacier 	942 bedrock 	908 iron 
	901 night black 	907 stone gray 	907 stone gray 
			
18003 natural white	18004 alabaster	18007 blue ice	18010 parchment
939 cool white 	939 cool white 	948 blueridge 	955 oyster white 
955 oyster white 	913 mineral gray 	944 steel blue 	933 sandrift 
933 sandrift 	905 pewter 	926 deep sea blue 	936 cool beige 
			
18013 cream beige	18014 pumice	18016 crystal rosa	18017 rose chocolate
934 butter 	937 bisque 	933 sandrift 	941 agate 
937 bisque 	954 adobe 	918 flax 	909 taupestone 
928 wheat 	902 deep suede 	905 pewter 	930 coffee 

Mannington's Edge Collection Wall Base features Optimum Edge (Type TS), Premium Edge (Type TP) and Mannington Edge (Type TV) in 2 1/2", 4" and 6" heights.

**Mannington Works.**

800 241 2262 [manningtoncommercial.com](http://manningtoncommercial.com)

Printed on recycled paper. Please help us close the loop by recycling this brochure or by sharing it with another individual.

300469

**MANNINGTON**  
COMMERCIAL