

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: MT-900 Solvent Cleaner

Chemical Name: Aliphatic ketones

Product Use/Class: Solvent cleaner for removing adhesives

Company Information: Mannington Mills, Inc.
P.O. Box 30 - Route 45
75 Mannington Mills Road
Salem, New Jersey 08079

Phone Numbers: Transport Emergency Contact:
Within the U.S. - CHEMTREC: (800) 424-9300
Outside the U.S. - CHEMTREC: +1-703-527-3887

General: (856) 935-3000
Product Emergency: (866) 359-5602

Effective Date: March 17, 2011

Supersedes Dates: January 6, 2009 [Rev. 2]
November 18, 2003

Reason for Revision: Product review and information updating

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight, %	Exposure Guidelines				
			ACGIH - TLV		OSHA - PEL		Other
			TWA	STEL	TWA	Ceiling	
Acetone	67-64-1	50-60	500 ppm	750 ppm	1000 ppm		
Methyl Ethyl Ketone	78-93-3	40-50	200 ppm	300 ppm	200 ppm		

SECTION 3 - HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Form: Clear liquid
Color: Colorless
Odor: Sweet ketone odor

WARNING STATEMENTS

DANGER! Extremely flammable liquid and vapor. Vapor harmful. Harmful or fatal if swallowed. Vapors may cause flash fire or explosion. Aspiration hazard if swallowed - can enter lungs and cause damage. Harmful if inhaled. KEEP OUT OF THE REACH OF CHILDREN.

POTENTIAL HEALTH EFFECTS

Primary Routes of Exposure: Eyes, skin, respiratory system.

Eye Contact: Can cause moderate to severe irritation, blurred vision, and eye damage. Vapors can cause slight to moderate irritation.

Skin Contact: Can cause moderate irritation, de-fatting, and dermatitis. Ingredients in Section 2 are absorbed through the skin into the blood upon contact.

Inhalation: Can cause nasal and respiratory irritation, including dizziness, weakness, fatigue, nausea, difficulty in breathing, headache, possible unconsciousness, and asphyxiation at high exposure levels.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. The possibility of aspiration of vapors into the lungs can lead to serious damage and chemical pneumonia.

Chronic: Overexposure to the components of this product has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver and kidney effects. Overexposure in humans: cardiac sensitization, kidney damage.

Other: No information.

Refer to Section 11 for toxicological information.

SECTION 4 - FIRST AID MEASURES

If in Eyes: Flush with water for 15 minutes. Get immediate medical attention.

If on Skin: Wash with soap and water. Call physician if irritation occurs.

If Inhaled: Move person to fresh air. Call physician immediately. If breathing stops, administer artificial respiration and get immediate medical attention.

If Swallowed: Do not induce vomiting. Call physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point (° F): - 4, TCC

Lower Explosive Limit (LEL) %: 2

Upper Explosive Limit (UEL) %: 13

Auto-Ignition Temperature: 760° F.

OSHA Flammability Classification: Class IB Flammable liquid.

Hazardous Products of Combustion: Material may produce CO, CO₂, H₂O, hydrocarbons, smoke, and materials listed in Section 2.

Extinguishing Media: Alcohol foam, CO₂, and dry chemical.

Unusual Fire and Explosion Hazards: Material is highly volatile and readily gives off vapors which may travel along the ground and be ignited by pilot lights, sparks, or other sources of ignition.

Fire Fighting Equipment: Wear self-contained breathing apparatus with a full face piece operated in positive pressure demand mode.

Miscellaneous Advice: None

Refer to Section 10 for additional information.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear protective clothing including appropriate respiratory gear.

Methods for Clean-up: Eliminate all ignition sources. Use spark proof tools and equipment. Dike and pump liquid to waste containers. Dispense sand, sawdust, or vermiculite and absorb spill residue. Shovel into secure containers of solvent proof construction. Do not allow into waterways, sewers, or storm drains.

Refer to Section 13 for disposal information.

Refer to Sections 14 and 15 for reportable quantity information.

SECTION 7 - HANDLING AND STORAGE

Handling: Use good hygienic practices. Do not open, dispense, or use around open flames, heat sources, or other sources of ignition. Large containers should be properly grounded during dispensing to avoid static discharge potential. Do not reuse containers. Do not puncture, drag, or slide container. Avoid prolonged or repeated breathing of vapor or mist. Reports have associated repeated or prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **KEEP CHILDREN AND PETS AWAY FROM WORK AREAS DURING USE OF THIS PRODUCT.**

Storage: Keep closures tight and containers upright to prevent leakage. Store in a cool, dry, well ventilated location. Store between 40 and 100 °F. Do not store near heat, sparks, or flame. Extinguish pilot lights. **STORE THIS PRODUCT AWAY FROM CHILDREN AND PETS.**

Consult the Mannington Professional Installation Handbook for additional information on handling and storage.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use sufficient ventilation, in volume and pattern, to keep air contaminant concentrations below PEL or TLV. Work areas must be free of all flame and ignition sources. Do not use in confined spaces without proper ventilation and personal protection.

Respiratory Protection: If PEL or TLV is exceeded, use a NIOSH/MSHA approved respirator, or a positive pressure supplied air respirator. Dust masks are not acceptable to prevent inhalation hazards.

Eye Protection: Wear splash goggles, face shield, and/or full face respirator if contact with liquid is likely.

Hand and Skin Protection: Wear solvent impermeable synthetic rubber gloves where contact with liquid is likely. Wear solvent resistant clothing where splash potential exists.

Other Protective Equipment: No information.

Hygienic Practices: Always wash hands before eating, smoking or using toilet facilities. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear thin liquid

Physical State: Liquid

Melting Point: Not applicable

Boiling Point (°F.): 131

Density: 0.79 grams/cm³

Vapor Density (Air = 1): 2.0 - 2.4

Specific Gravity (Water = 1.0): 0.79

Water Solubility: Moderately soluble

Volatiles (Wt. %): 100

VOC (Grams Per Liter): 790

Vapor Pressure (mm Hg@20°C.): 180

Evaporation Rate (Butyl Acetate = 1): 5.7

pH: Not applicable

Decomposition Temperature: No information

SECTION 10 - STABILITY AND REACTIVITY

Conditions to Avoid: Open flames, sparks, ignition sources

Materials to Avoid: Oxidizers

Stability: Stable

Hazardous Reactions: None known

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: See Section 5 - Products of Combustion.

SECTION 11 - TOXICOLOGICAL INFORMATION

Product LD₅₀ (Oral): Acetone (Rat) - 5800 mg/kg; LD_{Lo} (Man) -2857 mg/kg. Methyl Ethyl Ketone (Rat) - 2.7 - 5.6 g/kg, slightly toxic.

Product LD₅₀ (Dermal): Methyl Ethyl Ketone (Rabbit) - 5.0 - 13 g/kg, slightly toxic.

Product TC₅₀ (Inhalation): Acetone (Rat) - 44 mg/m³/4 hrs. TC_{Lo} (Man) - 500 ppm. Methyl Ethyl Ketone LC₅₀ (Rat) - Estimated > 5000 ppm/6 hrs, based in current studies.

Immediate (Acute) Effects: Acetone- Eye Irritation (Rabbit) 20 mg - Severe. Skin Irritation (Rabbit), 500 mg/24 hrs., Open Test - Mild.

Methyl Ethyl Ketone - Eye Irritation (Rabbit) 20 mg - Severe. Skin: Not a skin sensitizer based on human patch test.

Delayed (Subchronic & Chronic) Effects: No information.

SECTION 12 - ECOLOGICAL INFORMATION

Degradation: Solvent components readily volatilize when released to air, ground, or water. Bio-degradation in soil is gradual dependant on soil conditions. Degradation in air is via photochemical reaction (hydroxy radicals) with expected half lives of 22 days for acetone, and 5.5 days for methyl ethyl ketone. Little to no bioaccumulation is expected.

Ecotoxicity: Acetone: LC₅₀ (Rainbow Trout) - 5540 mg/L/96 hr. Sunfish, death - 14,250 ppm/24 hr. Methyl Ethyl Ketone: LC₅₀ (Fish) = 4600 - 5600 ppm. EC₅₀ (Invertebrates) = 1950 - 8890 ppm.

SECTION 13 - DISPOSAL CONSIDERATIONS

US EPA RCRA Status: Product: Ignitable hazardous waste, hazard category waste number – U002. Individual components hazardous waste numbers: Acetone – U002; Methyl Ethyl Ketone – U159.

Disposal Considerations: Dispose of as a flammable hazardous waste.

Disposal Method: Do not dispose at landfill. Dispose by incineration at permitted facility. Disposal should be done in accordance with all local, state and federal (40 CFR Part 261) regulations. Be aware that state and local requirements differ widely depending on location and may in many cases be different from federal rules.

SECTION 14 - TRANSPORT INFORMATION

The information provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment for transport.

Per 49 CFR 100-185, this material is classified as a “Consumer Commodity ORM-D”, as packaged.

U.S. DOT Proper Shipping Name: Consumer Commodity, ORM-D

Note: DOT-related information for shipping quantities larger than LTD QTY, use:

DOT Proper Shipping Name: Ketones, liquid, N.O.S. (Contains Acetone, Methyl Ethyl Ketone)

DOT Hazard Class: 3

DOT UN/NA Number: UN1224

Packing Group: PG II

Emergency Response Guide Number: 128

IMDG: UN1224, Ketones, Liquid, N.O.S. (Contains Acetone, Methyl Ethyl Ketone), Class 3, PGII

Emergency Response Guide Number: 128

IATA: Follow current IATA regulations and your carrier’s requirements.

SECTION 15 - REGULATORY INFORMATION

U.S. Federal Regulations:

CERCLA: Acetone RQ-5000 lbs. Methyl Ethyl Ketone RQ-5000 lbs.

Volatile Organic Compounds (VOC’s): Acetone, Methyl Ethyl Ketone

Hazardous Air Pollutants (HAP’s): Methyl Ethyl Ketone

SARA Section 311/312: Immediate (acute) health hazard; Delayed (chronic) health hazard; Fire hazard.

SARA Section 313: No components at or above EPA reporting thresholds.

Toxic Substances Control Act: All components are listed on the TSCA inventory.

Inventory Status: Listed

Export Notification: None

Other: California Proposition 65: Contains no components requiring notification.

SECTION 16 - OTHER INFORMATION

Hazard Ratings	Health	Fire	Reactivity	Additional Information
Suggested NFPA Rating	2	3	0	
Suggested HMIS Rating	2*	3	0	*Denotes potential chronic health hazard

Disclaimer:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date of hereof, the company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will the company be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

Legend:

N.E. - Not Established	S - Skin
N.A. - Not Available	ppm - Parts per Million
N/A - Not Applicable	° F. - Degrees Fahrenheit
C - Ceiling (Exposure Levels)	° C. - Degrees Centigrade
PEL - Permissible Exposure Limits	STEL - Short-Term Exposure Limit
OEL - Occupational Exposure Limit	CIH - Certified Industrial Hygienist
TSCA - Toxic Substances Control Act	TWA - Time Weighted Average
NFPA - National Fire Protection Association	
TLV - Exposure Limits Developed by ACCIH	
MSHA - Mine Safety and Health Administration	
NIOSH - National Institute for Occupational Safety	
OSHA - Occupational Safety and Health Administration	
HAZCOM - Hazard Communication Standard (29CFR1910.1200)	
ACGIH - American Conference of Government Industrial Hygienists	
CERCLA - Comprehensive Environmental Response, Comprehensive and Liability Act	