

primus  
framework  
lacosta



THIS DYNAMIC DUO OF

ORGANIC AND GEOMETRIC

STYLES WILL MAKE FIRST

AND LASTING IMPRESSIONS

WITH STYLE AND PERFORMANCE



Framework gives structure to the Lacosta pattern by incorporating subtle lines that intersect to form a geometric design ideal for any commercial environment

framework



ALL107 toasted sesame



ALL108 stone gray

Lacosta features delicate veins and swirls of color blended together to create a dramatic canvas in any space

lacosta



ALL131 suede



ALL126 taupestone



ALL129 fawn



ALL131 suede  
ALL109 mineral gray

## FEATURES

Primus brings together strength, durability and visual appeal with colors ranging from the subtle rich earthtones found in Framework to the lively hues of Lacosta.

Quantum Guard™ HP is Mannington's patented high performance wearlayer with a urethane aluminum oxide topcoat cured by a UV process. It is the industry's first true low maintenance floor providing superior appearance retention, cleanability, durability and slip retardance compared to standard resilient floors.

Quantum Guard™ HP can eliminate the need for polish over an extended period of time depending upon the amount of commercial traffic. While not rated for ramps, the Quantum Guard™ HP finish provides an enhanced level of traction and protection against slip compared to standard resilient floors.

Heterogeneous construction provides high performance for durability and strength. The Primus Collection will hold up to heavy rolling loads or high traffic areas with a 750 PSI.

Available in multiple widths – 6', 9', 12' – resulting in less waste, fewer seams and greater ease of installation.

Solid color weld rods are color-integrated with the Primus Collection to blend or create a monolithic appearance. They are also used to accent seams, enhance a border, outline an inset or used for wayfinding design.

Heat-welded seams provide an aseptic and integral surface that blocks the penetration of dirt and moisture. For optimal stain resistance performance, heat-welded seams should be sealed with a polish or sealer. Heat-weld is the preferred method for healthcare and high traffic environments.

Limited 5 Year Commercial Warranty. Limited 5 Year Quantum Guard™ HP Finish Warranty.



- Quantum Guard™ HP can eliminate the need for harsh cleaning agents, strippers and polishes due to its cleanability and durability
- Third party certified via the FloorScore IAQ testing program. FloorScore is an alternative compliance path to LEED EQ Credit 4.3.
- Meets CHPS 01350 IAQ test, passed and listed.
- Made in the USA - Manufactured in Salem, NJ 08079 and can contribute to LEED RM Credit 5.1 and 5.2.
- Adhesives meet VOC content limit of SCAQMD Rule #1168 and can contribute to LEED IEQ Credit 4.1.